

## Florida Approved

### Casement

Series	Depth	Operation	Thermal	Rating	Test Standard	Max Size	Impact	Florida Number
E2500	2 1/2"	Outswing	Strut	AW-95	AAMA 440-08	36" x 60"	No	FL17123.1
E3250	3 1/4"	Outswing	Strut	AW-95	AAMA 440-08	36" x 60"	No	FL17123.1
E4000	4"	Outswing	Strut	AW-95	AAMA 440-08	36" x 60"	No	FL17123.1

### Fixed

Series	Depth	Operation	Thermal	Rating	Test Standard	Max Size	Impact	Florida Number
3000	3"	None	PIP	AW-120	AAMA 440-08	60" x 99"	No	FL17121.2
3250	3.25"	None	PIP	DP-75	ASTM E 1886/1996	48 X 96	Yes	FL26945
3250	3.25"	None	PIP	AW-80	AAMA 101-08	60 X 99	No	FL26945
E2500	2 1/2"	None	Strut	AW-100	AAMA 440-08	60" x 99"	No	FL17121.4
E3250	3 1/4"	None	Strut	AW-100	AAMA 440-08	60" x 99"	No	FL17121.4
E4000	4"	None	Strut	AW-100	AAMA 440-08	60" x 99"	No	FL17121.4

### Fixed Offset

Series	Depth	Operation	Thermal	Rating	Test Standard	Max Size	Impact	Florida Number
E4000	4"	None	Strut	AW-80	AAMA 440-08	60" x 99"	No	FL 26945
E4000	4"	None	Strut	AW-120	AAMA 440-08	48" x 120"	No	FL 26945

### Hung

Series	Depth	Operation	Thermal	Rating	Test Standard	Max Size	Impact	Florida Number
3250	3.25"	Single	PIP	AW-75	AAMA 101-08	60 X 99	No	FL 26947
3250	3.25"	Single	PIP	DP-75	ASTM E 1886/1996	60 X 84	Yes	FL26947

### Project

Series	Depth	Operation	Thermal	Rating	Test Standard	Max Size	Impact	Florida Number
E2500	2 1/2"	Outswing	Strut	AW-90	AAMA 440-08	60" x 36"	No	FL17125.1
E3250	3 1/4"	Outswing	Strut	AW-90	AAMA 440-08	60" x 36"	No	FL17125.1
E4000	4"	Outswing	Strut	AW-90	AAMA 440-08	60" x 36"	No	FL17125.1