

Elite 2500 Project Out (2 1/2" Frame Depth)

Attributes

Family	Elite
Description	Elite 2500 Project Out (2 1/2" Frame Depth)
Frame Depth	2 1/2"
Frame Operation	Outswing
Thermal Type	Strut

Standrd Features

Architectural Grade Performance with AW-90 rating
1" insulated glass, IGCC-CBA rated, tested, and approved
Thermally broken frame and vent using strut technology
Frame and vent factory sealed to ensure weather tightness
Bead glazed for ease of replacement glass

Options

Available muntins include: true divided lites, between-the-glass, interior and exterior applied
1/4" single glazing up to 1 3/8" insulated glazing
Integral frame front flange
Lift out split sash
Mullion and stacking options
Receptor, subsill, and panning closure systems

Available Sizes

Rating	Minimum Size	Maximum Size
AW-90	20" x 16"	60" x 36"

Compatible Series

E2500 Fixed , E2500 Casement Outswing, E2500 Project Inswing

Accessories

2 1/2" Head & Jamb Closures (Strut), 2 1/2" Subsills (Strut), 2 1/2" Vertical Mullions, Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Screens, Stool Covers, Subsill Extenders