

Elite 2500 Casement Outswing (2 1/2" Frame Depth)

Attributes

Family	Elite
Description	Elite 2500 Casement Outswing (2 1/2" Frame Depth)
Frame Depth	2 1/2"
Frame Operation	Outswing
Thermal Type	Strut

Standard Features

- Architectural Grade Performance with AW-95 rating
- 1" insulated glass, IGCC-CBA rated, tested, and approved
- Thermally broken frame and vent using strut technology
- Frame factory sealed to ensure weather tightness
- Bead glazed for ease of replacement glass

Options

- Available muntins include: true divided lites, between-the-glass, interior and exterior applied
- 1/4" single glazing up to 1 3/8" insulated glazing
- Integral frame front flange
- Lift out split sash
- Mullion and stacking options
- Receptor, subsill, and panning closure systems

Available Sizes

Rating	Minimum Size	Maximum Size
AW-95	18" x 24"	36" x 60"

Compatible Series

E2500 Fixed , E2500 Project Outswing, E2500 Project Inswing

Accessories

2 1/2" Head & Jamb Closures (Strut), 2 1/2" Subsills (Strut), 2 1/2" Vertical Mullions, Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Screens, Stool Covers, Subsill Extenders