

## Elite 3250 Casement Outswing (3 1/4" Frame Depth)

### Attributes

Family	Elite
Description	Elite 3250 Casement Outswing (3 1/4" Frame Depth)
Frame Depth	3 1/4"
Frame Operation	Outswing
Thermal Type	Strut

### Standard Features

- Architectural Grade Performance with AW-95 rating
- 1" insulated glass, IGCC-CBA rated, tested, and approved
- Thermally broken frame and vent using strut technology
- Frame factory sealed to ensure weather tightness
- Bead glazed for ease of replacement glass

### Options

- Impact Wind Zone 4, Level D, ASTM E 1886/1996 - DP +70/-70 (36 X 60)
- 1/4 Inch single glazing up to 1 3/8 insulated glazing
- Integral frame front flange
- Lift out split sash
- Mullion and stacking options
- Receptor, subsill, and panning closure systems
- Available muntins include: true divided lites, between-the-glass, interior and exterior applied

### Available Sizes

Rating	Minimum Size	Maximum Size
DP-70	18" x 24"	36" x 60"
AW-95	18" x 24"	36" x 60"

### Compatible Series

E3250 Project Outswing, E3250 Fixed

### Accessories

3 1/4" Head & Jamb Closures (Strut), 3 1/4" Vertical Mullions, 3-1/4" Subsill, Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Screens, Stool Covers, Subsill Extenders