

Elite 3250 Project Out (3 1/4" Frame Depth)

Attributes

Family	Elite
Description	Elite 3250 Project Out (3 1/4" Frame Depth)
Frame Depth	3 1/4"
Frame Operation	Outswing
Thermal Type	Strut

Standard Features

- High performance with AW-90 rating
- Thermally broken frame and vent using strut technology
- Frame and vent extruded vinyl full perimeter seal to ensure weather tightness.
- Bead glazed for ease of replacement glass
- 1 Inch insulated glass, IGCC-CBA rated, tested, and approved
- Stainless steel non-handed heavy duty 4 bar hinges, AAMA tested to 904-09
- Single point, surface mount brush finished white bronze cam locks

Options

- Available muntins include: true divided lites, between-the-glass, interior and exterior applied
- 1/4" single glazing up to 1 3/8" insulated glazing
- Impact Wind Zone 4, Level D, ASTM E 1886/1996 - DP +70/-70 (48 X 48)
- Integral frame front flange
- Lift out split sash
- Mullion and stacking options
- Receptor, subsill, and panning closure systems
- Aluminum extruded 1.75" deep hinged screen

Available Sizes

Rating	Minimum Size	Maximum Size
AW-90	20" x 16"	60" x 36"
DP-70	20" x 16"	48" x 48"

Compatible Series

E3250 Casement Outswing, E3250 Fixed

Accessories

3 1/4" Head & Jamb Closures (Strut), 3 1/4" Vertical Mullions, 3-1/4" Subsill, Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Screens, Stool Covers, Subsill Extenders