

## Elite 3250 Fixed Frame (3 1/4" Frame Depth)

### Attributes

Family	Elite
Description	Elite 3250 Fixed Frame (3 1/4" Frame Depth)
Frame Depth	3 1/4"
Frame Operation	None
Thermal Type	Strut

### Standard Features

- Architectural Grade Performance with AW-100 rating
- Thermally broken frame using strut technology
- Frame factory sealed to ensure weather tightness
- Bead glazed for ease of replacement glass
- 1 Inch insulated glass, IGCC-CBA rated, tested, and approved

### Options

- Available muntins include: true divided lites, between-the-glass, interior and exterior applied
- 1/4" single glazing up to 1 3/8" insulated glazing
- Impact Wind Zone 4. Level D, ASTM E 1886/1996 - DP +70/-70 (48 X 72)
- Integral frame front flange
- Lift out split sash
- Mullion and stacking options
- Receptor, subsill, and panning closure systems

### Available Sizes

Rating	Minimum Size	Maximum Size
AW-100	12" x 12"	60" x 99"
DP-70	12" x 12"	48" x 72"

### Compatible Series

E3250 Casement Outswing, E3250 Project Outswing

### Accessories

3 1/4" Head & Jamb Closures (Strut), 3 1/4" Vertical Mullions, 3-1/4" Subsill (Strut), Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Stool Covers, Subsill Extenders