

Elite 4000 Casement Outswing (4" Frame Depth)

Attributes

Family	Elite
Description	Elite 4000 Casement Outswing (4" Frame Depth)
Frame Depth	4"
Frame Operation	Outswing
Thermal Type	Strut

Standard Features

Architectural Grade Performance with AW-95 rating
1"• insulated glass, IGCC-CBA rated, tested, and approved
Thermally broken frame and vent using strut technology
Frame and vent factory sealed to ensure weather tightness
Bead glazed for ease of glass replacement

Options

Available muntins include: true divided lites, between-the-glass, interior and exterior applied
1/4"• single glazing up to 1 3/8"• insulated glazing
Integral frame front flange
Lift out split sash
Hinged access panel with blinds
Mullion and stacking options
Panning closure systems

Available Sizes

Rating	Minimum Size	Maximum Size
AW-95	18" x 24"	36" x 60"

Compatible Series

E4000 Project Outswing, E4000 Fixed , E4000 Fixed Offset

Accessories

4" Frame Filler (Strut), 4" Head & Jamb Closures (Strut), 4" Subsills (Strut), 4" Vertical Mullions, Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Screens, Stool Covers, Subsill Extenders