

## Elite 4000 Offset Fixed Frame (4" Frame Depth)

### Attributes

Family	Elite
Description	Elite 4000 Offset Fixed Frame (4" Frame Depth)
Frame Depth	4"
Frame Operation	None
Thermal Type	Strut

### Standard Features

- Architectural Grade Performance with AW-80 / AW-120 ratings
- 1" insulated glass, IGCC-CBA rated, tested, and approved
- Thermally broken frame using strut technology
- Frame factory sealed to ensure weather tightness
- Bead glazed for ease of glass replacement
- Integral frame offset impost to simulate operable hung window

### Options

- Impact Wind Zone 4, Level D, ASTM E 1886/1996 DP +100/-100 (48 X 96)
- Mullion and stacking options
- Receptor, subsill, and panning closure systems
- Available muntins include: between-the-glass, or interior and exterior applied

### Available Sizes

Rating	Minimum Size	Maximum Size
AW-80	18" x 24"	60" x 99"
AW-120	18" x 24"	48" x 120"
DP-100	18" x 24"	48" x 96"

### Compatible Series

E4000 Project Outswing, E4000 Casement Outswing, E4000 Fixed

### Accessories

4" Frame Filler (Strut), 4" Head & Jamb Closures (Strut), 4" Subsills (Strut), 4" Vertical Mullions, Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Stool Covers, Subsill Extenders