

3250 Single Hung

Attributes

Family	3250
Description	3250 Single Hung
Frame Depth	3.25"
Frame Operation	Single
Thermal Type	PIP

Standard Features

- Commercial Grade Performance - AW-75 (60 X 99)
- 3-1/4 inch thermally broke frame and sash
- Integral nail fin frame with 1-1/8 inch setback
- Aluminum glazing beads to match window finish
- Sash has integral lift rail at sill and head
- Auto sill lock
- Sloped sill for exceptional water drainage
- Concealed side load block and tackle balances
- 1 inch insulated glass, IGCC-CBA rated, tested, and approved

Options

- Equal leg frame or integral front flange frame
- Impact Wind Zone 4, Level D - ASTM E 1886/1996 - DP +75/-85 (60 X 84)
- Class 5 Ultra-Lift balances
- Sweep locks at sash head
- Available muntins include: horizontal or vertical true muntins. Muntins between the glass
- Mullion and stacking options
- Receptor, subsill and panning closure systems
- 3/4 inch Insulated glass

Available Sizes

Rating	Minimum Size	Maximum Size
AW-75	18 X 24	60 X 99
DP-75	18 X 24	60 X 84

Compatible Series

3250 Fixed

Accessories

3 1/4 Head & Jamb Closures, 3 1/4" Vertical Mullions, 3-1/4" Subsill, Integral Louver Frame, Panning Trim, Stool Covers, Subsill Extenders