

E3062 Fixed Window

Attributes

Family	E3062
Description	E3062 Fixed Window
Frame Depth	3.25"
Frame Operation	None
Thermal Type	Strut

Standrd Features

Architectural Grade Performance with AW-100 Rating
Thermally broken frame using strut technology
Frame factory sealed to ensure weather tightness
Interior bead glazed for ease of replacement
1 inch insulated glass, IGCC-CBA rated, tested and approved

Options

Available muntin options include: true divided lites, between-the-glass, exterior and interior appllied
Available muntin options: true divided lite, between-the glass, exterior and interior applied
Mullion and stacking options
Receptor, subsill, and panning closure systems
Multiple configurations available with operable windows in one integral frame
Multiple Frame Options: Eq-Leg, Nail-Fin, Front Flange

Available Sizes

Rating	Minimum Size	Maximum Size
AW-100	12 X 18	60 x 99

Compatible Series

E3062 Casement Outswing, E3062 Project Outswing, E3062 Project Inswing

Accessories

3 1/4" Head & Jamb Closures (Strut), 3 1/4" Vertical Mullions, 3-1/4" Subsill (Strut), Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Subsill Extenders, Trim and Clip