

Florida Approved

Casement

| Series | Depth | Operation | Thermal | Rating | Test Standard | Max Size | Impact | Florida Number |
|--------|--------|-----------|---------|--------|---------------|-----------|--------|----------------|
| E2500 | 2 1/2" | Outswing | Strut | AW-95 | AAMA 440-08 | 36" x 60" | No | FL17123.1 |
| E3250 | 3 1/4" | Outswing | Strut | AW-95 | AAMA 440-08 | 36" x 60" | No | FL17123.1 |
| E4000 | 4" | Outswing | Strut | AW-95 | AAMA 440-08 | 36" x 60" | No | FL17123.1 |

Fixed

| Series | Depth | Operation | Thermal | Rating | Test Standard | Max Size | Impact | Florida Number |
|--------|--------|-----------|---------|--------|------------------|-----------|--------|----------------|
| 3250 | 3.25" | None | PIP | DP-75 | ASTM E 1886/1996 | 48 X 96 | Yes | FL26945 |
| 3250 | 3.25" | None | PIP | AW-80 | AAMA 101-08 | 60 X 99 | No | FL26945 |
| E2500 | 2 1/2" | None | Strut | AW-100 | AAMA 440-08 | 60" x 99" | No | FL17121.4 |
| E3250 | 3 1/4" | None | Strut | AW-100 | AAMA 440-08 | 60" x 99" | No | FL17121.4 |
| E4000 | 4" | None | Strut | AW-100 | AAMA 440-08 | 60" x 99" | No | FL17121.4 |

Fixed Offset

| Series | Depth | Operation | Thermal | Rating | Test Standard | Max Size | Impact | Florida Number |
|--------|-------|-----------|---------|--------|---------------|------------|--------|----------------|
| E4000 | 4" | None | Strut | AW-80 | AAMA 440-08 | 60" x 99" | No | FL 26945 |
| E4000 | 4" | None | Strut | AW-120 | AAMA 440-08 | 48" x 120" | No | FL 26945 |

Hung

| Series | Depth | Operation | Thermal | Rating | Test Standard | Max Size | Impact | Florida Number |
|--------|-------|-----------|---------|--------|------------------|----------|--------|----------------|
| 3250 | 3.25" | Single | PIP | DP-75 | ASTM E 1886/1996 | 60 X 84 | Yes | FL26947 |
| 3250 | 3.25" | Single | PIP | AW-75 | AAMA 101-08 | 60 X 99 | No | FL 26947 |

Project

| Series | Depth | Operation | Thermal | Rating | Test Standard | Max Size | Impact | Florida Number |
|--------|--------|-----------|---------|--------|---------------|-----------|--------|----------------|
| E2500 | 2 1/2" | Outswing | Strut | AW-90 | AAMA 440-08 | 60" x 36" | No | FL17125.1 |
| E3250 | 3 1/4" | Outswing | Strut | AW-90 | AAMA 440-08 | 60" x 36" | No | FL17125.1 |
| E4000 | 4" | Outswing | Strut | AW-90 | AAMA 440-08 | 60" x 36" | No | FL17125.1 |

Slider

| Series | Depth | Operation | Thermal | Rating | Test Standard | Max Size | Impact | Florida Number |
|--------|-------|------------|---------|--------|-----------------------|----------|--------|----------------|
| 3250 | 3.25" | Horizontal | PIP | AW-50 | AAMA/WDA/CSA 101/A440 | 72 X 72 | Yes | FL 29258 |