

Elite 4000 Casement Outswing (4" Frame Depth)

Attributes

Family	Elite
Description	Elite 4000 Casement Outswing (4" Frame Depth)
Frame Depth	4"
Frame Operation	Outswing
Thermal Type	Strut

Standard Features

- Architectural Grade Performance with AW-95 rating
- 1"• insulated glass, IGCC-CBA rated, tested, and approved
- Thermally broken frame and vent using strut technology
- Frame and vent factory sealed to ensure weather tightness
- Bead glazed for ease of glass replacement

Options

- Available muntins include: true divided lites, between-the-glass, interior and exterior applied
- 1/4"• single glazing up to 1 3/8"• insulated glazing
- Integral frame front flange
- Lift out split sash
- Hinged access panel with blinds
- Mullion and stacking options
- Panning closure systems

Available Sizes

Rating	Minimum Size	Maximum Size
AW-95	18" x 24"	36" x 60"

Compatible Series

E4000 Project Outswing, E4000 Fixed , E4000 Fixed Offset

Accessories

4" Frame Filler (Strut), 4" Head & Jamb Closures (Strut), 4" Subsills (Strut), 4" Vertical Mullions, Exterior Applied Grids, Head & Jamb Closure Extenders, Panning Trim, Screens, Stool Covers, Subsill Extenders